



Ideal to give your shop or establishment a professional image



Evolis Black PVC cards are the ideal support for your tags. PVC cards are an easy, hygienic and aesthetics way to manage your communication and to strengthen your brand image. The matte black cards printed in white will assure you a chalkboard finish for your labels. Evolis plastic cards support the requirements of the food industry.

ADVANTAGES

Using Evolis High Trust® cards allows an optimal printing quality and a good readability of specific elements (texts, barcodes, images, etc.). Made from PVC, they are flexible but very resistant and solid.

Additionally, our PVC cards are dedicated to use in the food industry, they are ideal for price tag labelling (bakers, butchers, supermarkets, etc.).

Tested and validated by Evolis R&D and Quality departments, these consumables bring you printing quality and reliability.

GENERAL SPECIFICATIONS

- · Cards in PVC Blank Black Matte finish
- · Compliant with ISO CR-80 (ISO 7810) standards
- Dimension: 85.6 mm Length x 54 mm Width (3 3/8" x 2 1/8")
- · Thickness: 0.76 mm / 30 mil



PRODUCT INFORMATION:

- PVC Cards
- · Blank Black Matte finish
- •30 MIL



COMPATIBILITY AND PACKAGING

PART#	PACKAGE	EDIKIO ACCESS	EDIKIO FLEX / EDIKIO DUPLEX	ZENIUS / PRIMACY	PRIMACY2	QUANTUM2
C8001	5 boxes of 100 cards, film wrapped			٠	•	٠

STORAGE INFORMATION

The cards shall be capable of functioning for up to 2/3 years after purchase if stored in a cool, dry environment and having remained unopened from the original packaging.

Temperature of storage must be between 5-40°C (41-104°F) and at RH between 10-60%.

Once opened, avoid dust, direct sunlight, high humidity and high temperatures.

Do not place near solvent or other chemicals.

INSTRUCTIONS FOR USE

In order to optimize the printing quality and card durability:

- · Do not print cards that are damaged, folded, dirty or deformed.
- · Avoid touching the printable surface of the cards to preserve print quality.
- Do not expose tags to strong sources of heat (deterioration possible from 60 $^{\circ}$ C / 140 $^{\circ}$ F). Avoid thermal shocks.
- · Avoid putting the printed labels in contact with fatty substances.
- Do not clean the tags in a machine, with boiling water or abrasive detergent products.

 Preference should be given to cleaning with warm water (<60°C / 140°F) or with a neutral detergent diluted with water, and a microfibre cloth. Dry the tags thoroughly before using them.